PRODUCT DATA SHEET

Hodgson

AS75 GLUESTRIP

Version No.2	Revision Date: 05/06/09	Page 1 of 2

DESCRIPTION

A pressure sensitive rubber resin adhesive for bonding difficult substrates such as polyethylene and polypropylene. An excellent adhesive on a roll.

KEY FEATURES

Very high surface tack, adheres well to most building surfaces including polyethylene and polypropylene.	Made of inert materials, does not set or cure after placement in joint.
Extremely strong and tacky, this product has an enormous variety of bonding applications. Sticks well to a wide variety of surfaces.	Easy to apply.

USES

Joining polyethylene sheets.	Bonding kick plates.
Making products self-adhesive.	Mounting lightweight items.
External low to medium movement joints between brick, concrete and timber.	

PERFORMANCE

Density: 0.98g/cm^3 **Tensile Strength**: 55N/cm^2 **Service temperature range:** -10ºC to +40ºC	**Shrinkage:** <1% **Elongation:** >1000%. **Staining:** Nil

APPLICATION

PROPERTIES

Application temperature range: +10ºC to +40ºC

Shelf life: 12 months when stored flat in original packaging in cool, dry conditions. Do not store below 5ºC

INSTRUCTIONS

Surface preparation: All surfaces should be clean, dry and free from frost, grease and loose materials. When cleaning contaminated substrates, Hodgson recommend that propan-2-ol (IPA) is used and allowed to dry prior to the application of the sealant strip. Timber surfaces should be coated with at least one coat of a base stain or paint primer and allowed to fully dry prior to application of AS75 Gluestrip.

Application: Apply adhesive face down to one of the surfaces in the required position. Remove backing paper and apply other surface onto AS75 pushing firmly to ensure good contact with full area of strip along the length of the joint.

PACKAGING

12 x 0.4mm (30m) x 44 reels	Available colour: Honey

Hodgson Sealants Limited Belprin Road, Beverley, East Yorkshire, HU17 0LN, United Kingdom
T: +44 (0)1482 868321
F: +44 (0)1482 870729
W: www.hodgsonsealants.com
E: sales@hodgsonsealants.com

Registered in England No. 2799221 | Registered Office. Belprin Road, Beverley, East Yorkshire, HU17 0LN, United Kingdom | VAT REG. No. GB 856 3436 07

GENERAL

AS75 Gluestrip is part of a full range of speciality sealants and tapes designed for the professional user. For further information please contact our Customer Care Team or visit our Website.

The information given in this product data sheet is based on laboratory tests and experience which we believe to be correct. Properties quoted are typical and do not therefore constitute a specification. In view of the wide range and variability of substrates, we would advise that our product should be tested by the user to establish suitability for its intended application. E &OE.

Hodgson Sealants Limited

Belprin Road, Beverley, East Yorkshire,
HU17 0LN, United Kingdom

T: +44 (0)1482 868321
F: +44 (0)1482 870729

W: www.hodgsonsealants.com
E: sales@hodgsonsealants.com

Registered in England No. 2799221 | Registered Office. Belprin Road, Beverley, East Yorkshire, HU17 0LN, United Kingdom | VAT REG. No. GB 856 3436 07