# PRODUCT DATA SHEET

Hodgson

## SEALANT APPLICATION EQUIPMENT

| Version No.2 | Revision Date: 14/07/09 | Page 1 of 3 |
|---|---|---|

| Order Code | Product Name | Picture | Suitable for use with |
|---|---|---|---|
| 1560 | Easyflow HD<br>Economy Skeleton Gun | | 310ml<br>Cartridges |
| 1561 | Easyflow HD<br>Economy Skeleton Gun | | 380/400ml<br>Cartridges |
| 1562 | Powerflow Cartridge HP<br>High Powered Skeleton Gun<br><br>Easy on the hands – good for filling deep joints. | | 310ml & 400ml<br>Cartridges |

**Hodgson Sealants Limited**
Belprin Road, Beverley, East Yorkshire, HU17 0LN, United Kingdom
T: +44 (0)1482 868321
F: +44 (0)1482 870729
W: www.hodgsonsealants.com
E: sales@hodgsonsealants.com

Registered in England No. 2799221 | Registered Office. Belprin Road, Beverley, East Yorkshire, HU17 0LN, United Kingdom | VAT REG. No. GB 856 3436 07

| Order Code | Product Name | Picture | Suitable for use with |
|---|---|---|---|
| 1566 | Airflow II Cartridge<br>Pneumatic Gun | | 310ml Cartridges<br><br>OR<br><br>400ml Cartridges |
| 1567 | Powerflow Combi HP<br>Manual Gun<br><br>Easy on the hands – good for filling deep joints. Includes nozzle holder. | | 400ml & 600ml<br>Sachets |
| 1568 | Airflow II Sachet<br>Pneumatic Gun<br><br>Ideal for indoor applications where noise levels less than 70db are crucial.<br>Includes nozzle holder | | 400ml & 600ml<br>Sachets |

| Order Code | Product Name | Picture | Suitable for use with |
|---|---|---|---|
| 9950 | White Cone Nozzle | | 1566 Gun<br>1570 Gun |
| 9951 | Red Screw in Nozzle | | 1567 Gun<br>1568 Gun<br>1574 Gun |
| 9983 | Spare Nozzle Holder | For use with Screw in Nozzles | |
| 9986 | Spare Sachet Plunger/cord Assembly | Available to order – please specify Gun Name | |

*The information given in this product data sheet is based on laboratory tests and experience which we believe to be correct. Properties quoted are typical and do not therefore constitute a specification. In view of the wide range and variability of substrates, we would advise that our product should be tested by the user to establish suitability for its intended application. E &OE*