PRODUCT DATA SHEET

Hodgson

TIMBER SEALER

Version No.2	Revision Date: 31/03/09	Page 1 of 1

DESCRIPTION

Quick drying brush applied sealer for timber surfaces.

KEY FEATURES

Ready to use high quality timber sealer.	The preferred choice of many professional glaziers.
Compatible with Hodgson Butyl 66 and Colourglaze compounds.	

USES

If the timber surface is not sealed with the recommended sealer, the service life of the glazing products will be substantially reduced.

APPLICATION

PROPERTIES

Application temperature range: +5ºC to +30ºC

Shelf life: 12 months when stored in original packaging in cool, dry conditions away from direct sunlight.

INSTRUCTIONS

Application: Ensure surfaces are clean, dry and free from loose materials before application. Apply two coats of sealer by brush to the rebate and those surfaces of the bead which will be in contact with the glazing compound. Allow to dry (about 15mins) before applying the glazing compound or a further coat. Wash brushes in propan-2-ol (IPA) solvent.

PACKAGING

750ml bottle – 12 per carton.

GENERAL

Timber Sealer is part of a full range of cleaning products, tools and consumables for the Glass & Glazing market. For further information please contact our Customer Care Team or visit our Website.

The information given in this product data sheet is based on laboratory tests and experience which we believe to be correct. Properties quoted are typical and do not therefore constitute a specification. In view of the wide range and variability of substrates, we would advise that our product should be tested by the user to establish suitability for its intended application. E &OE.

Hodgson Sealants Limited
Belprin Road, Beverley, East Yorkshire, HU17 0LN, United Kingdom
T: +44 (0)1482 868321
F: +44 (0)1482 870729
W: www.hodgsonsealants.com
E: sales@hodgsonsealants.com

Registered in England No. 2799221 | Registered Office. Belprin Road, Beverley, East Yorkshire, HU17 0LN, United Kingdom | VAT REG. No. GB 856 3436 07