PRODUCT DATA SHEET

Hodgson

FLEECEBAND 0318

Version No.2	Revision Date: 14/01/09	Page 1 of 2

DESCRIPTION

Fleeceband 0318 is a synthetic rubber-based preformed strip sealant laminated with a non-woven polyester fleece.

KEY FEATURES

Good adhesion to a wide range of substrates.	Remains flexible throughout its service life.
The product is highly conformable.	Easy and accurate to use with little waste and no mess.
The fleece will accept paint, plaster, cement and adhesives.	

USES

For sealing floor-to-wall joints and around drains in wetrooms.	For sealing cracks prior to plastering.
For sound-deadening applications.	For applications to prevent air-leakage.

PERFORMANCE

	UNIT	NOMINAL VALUE	TEST METHOD
Dynamic Shear Adhesion	N/cm^2	12	H15
90° Peel Adhesion	N/cm	8	H48
180° Peel Adhesion	N/cm	9	H41
Specific Gravity	g/cm^3	1.6	H6
Moisture Vapour Transmission Rate	$g/m^2/24hr/mm$	0.18	ISO9932 / BS ISO 15106
Service Temperature Range	°C	-40 to +90	

H – Hodgson Test Method

Hodgson Sealants Limited
Belprin Road, Beverley, East Yorkshire, HU17 0LN, United Kingdom
T: +44 (0)1482 868321
F: +44 (0)1482 870729
W: www.hodgsonsealants.com
E: sales@hodgsonsealants.com

Registered in England No. 2799221 | Registered Office. Belprin Road, Beverley, East Yorkshire, HU17 0LN, United Kingdom | VAT REG. No. GB 856 3436 07

APPLICATION

PROPERTIES

Application temperature range: +5°C to +40°C

Shelf life: 24 months when stored flat in original packaging in cool, dry conditions.

INSTRUCTIONS

Surface preparation: All surfaces should be clean, dry and free from frost, grease and loose materials. When cleaning contaminated substrates, Hodgson recommend that propan-2-ol (IPA) is used and allowed to dry prior to the application of the sealant strip. When applying the tape to porous or friable surfaces, it is recommended that the surface be treated with a suitable primer, such as an exterior grade PVA, to seal and stabilise the surface.

Application: Remove the release paper and apply the tape to the substrates to be joined. Take care to avoid rucks in the tape. Roll the tape with a small roller to ensure good adhesion along the whole length of the tape.

PACKAGING

The product is normally supplied as a preformed strip on a siliconised release paper. A wide range of dimensions can be supplied. Diecut parts can be supplied for this product. Product dimensions will determine the number of rolls per carton.	Available sealant colours: Black or grey.

TOLERANCES

Thickness ± 10%

Width: up to 25mm ± 1mm

26mm to 100mm ± 2mm

over 100mm ± 3mm

GENERAL

Fleeceband 0318 is part of a range of sealant products for Construction & Automotive Markets. For further information, please contact our Customer Care Team or visit our Website.

The information given in this product data sheet is based on laboratory tests and experience which we believe to be correct. Properties quoted are typical and do not therefore constitute a specification. In view of the wide range and variability of substrates, we would advise that our product should be tested by the user to establish suitability for its intended application. E &OE.

Hodgson Sealants Limited

Belprin Road, Beverley, East Yorkshire, HU17 0LN, United Kingdom

T: +44 (0)1482 868321
F: +44 (0)1482 870729

W: www.hodgsonsealants.com
E: sales@hodgsonsealants.com

Registered in England No. 2799221 | Registered Office. Belprin Road, Beverley, East Yorkshire, HU17 0LN, United Kingdom | VAT REG. No. GB 856 3436 07