PRODUCT DATA SHEET

Hodgson

FOILBAND 0346

Version No.2	Revision Date: 14/01/09	Page 1 of 2

DESCRIPTION

Foilband 0346 is a synthetic rubber-based preformed strip sealant laminated with a fixed foil backing and with a filmic release liner.

KEY FEATURES

Good adhesion to a wide range of substrates.	Remains flexible throughout its service life.
The product is highly conformable.	Good UV resistance.
The foil has good tear resistance.	Easy and accurate to use with little waste and no mess.
The product has a filmic release liner that overcomes potential tear issues often associated with paper release liners.	

USES

For sealing over joins of liner panels (helps compliance with Part L2 of UK Building Regulations)	For sealing of joints as a barrier against moisture vapour.
For sealing over T-bars in glazing and conservatories.	

PERFORMANCE

	UNIT	NOMINAL VALUE	TEST METHOD
Dynamic Shear Adhesion	N/cm^2	12	H15
90° Peel Adhesion	N/cm	7	H48
180° Peel Adhesion	N/cm	8	H41
Specific Gravity	g/cm^3	1.7	H6
Moisture Vapour Transmission Rate (sealant component only)	$g/m^2/24hr/mm$	0.17	ISO9932 / BS ISO 15106
Service Temperature Range	°C	-40 to +90	

H – Hodgson Test Method

Hodgson Sealants Limited
Belprin Road, Beverley, East Yorkshire, HU17 0LN, United Kingdom
T: +44 (0)1482 868321
F: +44 (0)1482 870729
W: www.hodgsonsealants.com
E: sales@hodgsonsealants.com

Registered in England No. 2799221 | Registered Office. Belprin Road, Beverley, East Yorkshire, HU17 0LN, United Kingdom | VAT REG. No. GB 856 3436 07

APPLICATION

PROPERTIES

Application temperature range: +5°C to +40°C

Shelf life: 24 months when stored flat in original packaging in cool, dry conditions.

INSTRUCTIONS

Surface preparation: All surfaces should be clean, dry and free from frost, grease and loose materials. When cleaning contaminated substrates, Hodgson recommend that propan-2-ol (IPA) is used and allowed to dry prior to the application of the sealant strip. When applying the tape to porous or friable surfaces, it is recommended that the surface be treated with a suitable primer, such as an exterior grade PVA, to seal and stabilise the surface.

Application: Remove the backing film and apply the tape to the joint to be covered. Once applied in place, use a roller to ensure good adhesion to the substrate. Avoid joins in the flashing where possible. Any joins should overlap by at least 120mm, and be made with the uppermost piece overlapping on top of the lower strip, so that any water running down will drain freely over the front surface of the flashing.

PACKAGING

The product is normally supplied as a preformed strip on a siliconised release film. Product dimensions will determine the number of rolls per carton.

Width: 40mm up to 150mm

Thickness: 0.7mm or 1.0mm

Length: 10m or 20m

Available foil colours: Aluminium.

The sealant colour is black or grey.

TOLERANCES

Thickness ± 10%

Width: 40mm to 100mm ± 2mm

over 100mm ± 3mm

GENERAL

Foilband 0346 is part of a range of sealant products for Roofing and Glass & Glazing Markets. For further information, please contact our Customer Care Team or visit our Website.

The information given in this product data sheet is based on laboratory tests and experience which we believe to be correct. Properties quoted are typical and do not therefore constitute a specification. In view of the wide range and variability of substrates, we would advise that our product should be tested by the user to establish suitability for its intended application. E &OE.

Hodgson Sealants Limited

Belprin Road, Beverley, East Yorkshire, HU17 0LN, United Kingdom

T: +44 (0)1482 868321
F: +44 (0)1482 870729

W: www.hodgsonsealants.com
E: sales@hodgsonsealants.com

Registered in England No. 2799221 | Registered Office. Belprin Road, Beverley, East Yorkshire, HU17 0LN, United Kingdom | VAT REG. No. GB 856 3436 07